### The Hurricane-Flood-Landslide Continuum – Forecasting Hurricane Effects at Landfall

J. H. Golden<sup>a\*</sup>, E.I. Tollerud<sup>b</sup>, A. Negri<sup>c</sup>, R. Updike<sup>d</sup>

<sup>a</sup> Forecast Systems Laboratory, Boulder, CO 80305-3328, USA – (Joe.Golden@noaa.gov)

<sup>b</sup> Forecast Systems Laboratory, Boulder, CO 80305-3328, USA – (<u>edward.tollerud@noaa.gov</u>) <sup>c</sup> Goddard Space Flight Center, Greenbelt, MD, 20771, USA – (<u>Negri@agnes.gsfc.nasa.gov</u>)

<sup>d</sup> U.S. Geological Survey, Denver Federal Center, Denver, CO, 80225, USA – (updike@usgs.gov)

### ABSTRACT

In the 10 days of 21-30 September 1998, Hurricane Georges left a trail of destruction in the Caribbean region and U.S. Gulf Coast. Subsequently, in the same year, Hurricane Mitch caused widespread destruction and loss of life in four Central American nations, and in 1999 a tropical depression impacted the north coast of Venezuela causing hundreds of deaths and several million dollars of property loss. In each instance, the tropical system served as the catalyst for major flooding and landslides at landfall. Our goal is to develop and transfer an end-to-end warning system for a prototype region in the Central Caribbean, specifically the islands of Puerto Rico and Hispaniola. The envisioned system would include satellite and surface-based observations to track and nowcast dangerous levels of precipitation, atmospheric and hydrological models to predict short-term runoff and streamflow changes, geological models to warn when and where landslides and debris flows are imminent, and the capability to communicate forecast guidance products via satellite to vital government offices in Puerto Rico, Haiti, and the Dominican Republic.

KEYWORDS: cyclonic low-pressure systems, landslide/flood modeling, satellite-based rainfall estimates, integrating complementary agencies, flood forecasting technologies

## 1. INTRODUCTION: THE NEED: WARNINGS TO POTENTIAL FLOOD AND LANDSLIDE VICTIMS

During the past several years, the United States Geological Survey (USGS) and the National Oceanic and Atmospheric Administration (NOAA) have been called upon to respond to catastrophic floods and landslides throughout the United States triggered by intense meteorological phenomena. In the meantime, the National Aeronautics and Space Administration (NASA) has employed numerous satellite platforms to observe and monitor these Earth For the most part, each of these systems. agencies has used its own set of skills and capabilities to better understand the atmospheric processes involved in the cyclonic storms, the associated heavy precipitation, and the associated effects at landfall.

\*Corresponding author: Dr. Joseph H. Golden, Forecast Systems Laboratory, 325 Broadway, Boulder, CO 80305-3328; email Joe.Golden@noaa.gov; phone 303-497-6098.

floods and landslides. Cyclonic low-pressure systems reaching landfall along the Pacific Ocean states and extending inland to the east, as well as hurricane and tropical low-pressure systems from the Atlantic impinging on the southern and eastern coastal states, are the most frequent causes of these disasters. In some instances, the greatest loss of life and property is the direct result of the storm because of the high winds and heavy rains. But, in many cases, the greatest losses come from ground failures and floods.

Because the majority of our population lives in states bordering the Atlantic Ocean, Pacific Ocean, and the Gulf of Mexico, our exposure to landslide and flood disasters is of extreme concern; furthermore, unlike volcanoes and earthquakes, the hazard returns every year.

Hurricanes, typhoons, and cyclones strike Central American, Caribbean, Southeast Asian and Pacific Island nations even more frequently than the U.S. The global losses of life and property from the floods, landslides, and debris flows caused by cyclonic storms are staggering. One of the keys to reducing these losses, both in the U.S. and internationally, is to have better forecasts of what is about to happen from several hours to days before the event. Particularly in developing nations where science, technology, and communication are limited, advance-warning systems can have great impact. In developing countries, warnings of even a few hours or days can mitigate or reduce catastrophic losses of life.

For example, during late October 1998, Hurricane Mitch formed in the southwestern Caribbean and slowly intensified as it moved west-northwestward. Mitch eventually reached Category 5 status, with maximum winds of 180 mph and the fourth-lowest central pressure ever measured in an Atlantic hurricane. This immense storm literally engulfed Central America, where it remained almost stationary for several days, drawing moisture both from the Pacific Ocean and the Caribbean Sea. The countries of Guatemala, Honduras, El Salvador, and Nicaragua, in particular, were deluged with up to 933 mm of rain (Hellin and Haigh, 1999), triggering intense floods and thousands of landslides. In one instance alone, at least 2000 people from a single village were buried alive by a massive mudflow that traveled 13 miles down the slope of the Casitas volcano in northwestern Nicaragua. Hurricane Mitch eventually became the second most deadly Atlantic Hurricane in 200 years, killing over 9000 people and causing many billions of dollars in loss.

It appears that even though warnings for dangerously heavy rainfall were released by NOAA during Mitch, much of this information never reached local municipal officials in the Central American countries due to inadequate communication networks. In addition, the countries impacted the most have inadequate national weather services. It is likely that these countries were devastated far worse than otherwise would have been the case if each country had been better informed and prepared.

The United States now has the elements of science and technology that can make a profound difference in these potential disasters...

The essence of our vision is that we can develop the tools that will allow the United States to issue forecast guidance products for floods and landslides associated with the onset of major storms, and disseminate this guidance to local government entities well before the floods and slides begin.

To accomplish this vision, NOAA, USGS, and NASA are prepared to combine their respective scientific and technical talents. NOAA has the capability to provide highly reliable tracking and prediction of storm rainfall, trajectory, and landfall. USGS has the capability to evaluate beforehand the ambient stability of natural and man-made landforms, to assess landslide susceptibilities for those landforms, and to establish probabilities for initiation of landslides and debris flows. In addition, USGS is widely recognized as a leader in the study of the interrelationship of vegetation, ambient stream flow, ground water, soil moisture, and geologic conditions in assessing the potential for floods. NASA, NOAA, and USGS are all currently actively developing precipitation-flood forecasting technologies. NOAA-NWS has a successful history of developing technologies aimed at rapid dissemination of weather threat data. NASA has great capacity to monitor and evaluate various natural phenomena occurring at the Earth's surface. With its multiple satellite platforms and remote sensing devices on board these satellites, NASA provides the United States with sophisticated rainfall mapping for severe storms and hurricanes. All three agencies have a long history of work on natural hazards both domestically and overseas.

Although all three agencies are conducting research on their respective aspects of this

problem, there is currently no mechanism to integrate potentially complementary the A proposed project, called the programs. Hurricane-Flood-Landslide Continuum project, will bring together the three agencies to utilize their understanding of the range of scenarios of land surface instability (landslides and floods) as a result of specific evolving meteorological conditions. The problem is extremely complex, but scientists in USGS, NASA, and NOAA are convinced that the tools can be developed to substantially reduce the risk from hurricanes at Elsberry landfall. (2002)has recently summarized progress on predicting hurricane landfall precipitation.

## 2. THE RESPONSE: AN END-TO-END PREDICTION SYSTEM FOR HEAVY RAINFALL, FLOODING, AND LANDSLIDES

With the foregoing needs in mind, NOAA's Systems Laboratory Forecast (FSL) is collaborating on the Continuum project to initially develop and transfer a warning system for a prototype region in the Central Caribbean, specifically the islands of Puerto Rico and Hispaniola. The system will include satellite observations to track and nowcast dangerous levels of precipitation, hurricane tracking information from NOAA's National Hurricane Center, atmospheric and hydrological models to predict near-future runoff and streamflow changes in affected regions, and landslide models to warn when and where landslides and debris flows are imminent. See Elsberry (2002) for a recent summary of hurricane landfall precipitation forecast models. Since surface communications are likely to be interrupted during these crises, the project also includes the capability to communicate disaster information via satellite to vital government officials in Puerto Rico, Haiti, and Dominican Republic. In the initial phase of this project, studies of Mitch, Georges, and other recent hurricanes using satellite data and ground-based observations will be made to assess how the proposed forecast systems would have improved response and recovery in those devastating events.

Developed over a three-year period, this forecast system will provide important, immediate applications to short-term prediction and warning of flooding and landslides in the prototype region, and the science and technology can easily be applied in the United worldwide. States and The information deliverables for the prototype region will be tailored to the societal and economic needs of the affected countries, and will be carefully monitored and documented at the local level in order to provide feedback from forecasters and officials to the NASA-NOAA-USGS science team.

To provide necessary objective assessment of the progress and quality of the forecast system, NOAA will enhance its Real-Time Verification System (RTVS; Mahoney et al, 2002), so that the developers and users can easily assess verification results through an interactive, Webbased, graphical user interface.

# 3. THE END PRODUCT: A SYSTEM APPROACH

The focus of the Continuum project is to improve our ability to predict the evolution of the Earth system in both a prognostic and retrospective sense. It is based on an approach that integrates more than one of the traditional Earth science disciplines, and encourages innovation and complementary use of models and data from multiple satellites and sensors.

The key components of the Continuum project are:

- A comprehensive, real-time data acquisition system (ground surface monitors, radar, infrared and microwave satellites, upper-air observations, etc.)
- A relocatable, multinested weather data analysis system suitable for various terrains and environments
- A high-resolution multinested weather forecast model component for ground surface precipitation prediction
- A hydrological modeling component for peak streamflow and flow duration

- Landslide and debris flow model components that are tuned to geology and ambient conditions
- An interactive, multitiered, redundant, multihazard warning communication system
- Societally relevant governmental decision-support systems
- Long-term capacity-building through training for both scientific and governmental personnel

A conceptual flow diagram showing principal tasks and those responsible is shown in Figure 1. Although there is a natural linear progression whereby the output of one element forms the input to another, it is also clear that each must be closely coordinated with several others. This is particularly true for the FSL World Wide Weather Workstation, which must be equipped to accept quite different forms of input ranging from satellite-derived fields of precipitation to runoff from an individual river basin. Similarly, FSL's Local Analysis and Prediction



Figure 1. Conceptual flow-chart of key responsible scientists/tasks for major tasks required to fulfill major outputs of Continuum project. Note that some of these tasks will have to be done in parallel, with close connectivity in real time.

System (LAPS) shares a need for appropriate satellite data for rain estimation with the Quantitative Precipitation Estimation component (McGinley et al., 1991); it thus makes sense that these two products be compatible and consistent. Compatibility between the temporal scales of the LAPS analyses and predictions and those required by the input fields to the runoff models in the hydrology component must also be assured. Since the groups preparing these individual products are located in near proximity to FSL, developing this compatibility should be relatively effortless.

Careful integration of the NOAA, NASA, and USGS elements will also be necessary. For instance, terrain data necessary for landslide modeling is also a critical element in hydrological modeling, and accurate soil moisture content, a key variable for landslide modeling, is also vital as input to the hydrological and atmospheric models. NASA, NOAA and USGS will combine their technologies to allow integrated displays of the landslide, atmospheric, and hydrologic models, all of which should be available simultaneously and compatibly, via a shared Graphical Information System (GIS). Building these links will have lasting advantages for collaboration and decisionmaking beyond the scope of the initial project.

#### 4. RETROSPECTIVE CASE STUDIES

A recent example of NASA's rainfall estimation mapping for Tropical Storm Bill after its landfall in southern Louisiana is shown in Figure 2. After coming ashore



Figure 2. Storm-total precipitation map for Tropical Storm Bill based on TRMM satellite data.

Monday, 30 June, just east of Morgan City Louisiana, as a tropical storm, the remnants of Bill continued to produce heavy rain throughout the southeastern U.S. and mid-Atlantic region as the system tracked off to the northeast. The heaviest rainfall totals were along the Gulf Coast on the eastern side of where Bill made landfall, as seen in the TRMM-based (Tropical Rainfall Measuring Mission) near real-time Multisatellite Precipitation Analysis (MPA) at the NASA Goddard Space Flight Center (Huffman et al., 2003). TRMM is a joint mission between NASA and the National Space Development Agency of Japan (NASDA). Some areas from western Louisiana to the Florida panhandle received upwards of 250 mm of rain, as depicted by the TRMM-based MPA, in good agreement with local radar estimates. The low pressure center associated with Bill tracked northeastward across western Louisiana. southern Mississippi, and central Alabama before merging with a stationary front over the western Carolinas. Broad areas of 60-100 mm rainfall amounts were observed from northern Alabama and central Georgia through the Carolinas and into northern Virginia with locally heavier amounts of 100-190 mm. Fortunately, the remnants of Tropical Storm Bill moved steadily across the southeast-keeping rainfall amounts from being even higher. Estimates such as these will be further improved by blending NEXRAD radar estimates and surface raingauge data.

As another retrospective case study, we propose to apply existing datasets for Hurricane Georges as it passed over the islands of Puerto Rico and Hispaniola, as well as another extreme precipitation event, the Venezuelan flooding/landslides of December 1999. Up to 760 mm rainfall was estimated over Puerto Rico in 24 h, during the passage of Hurricane Georges (Padgett, 1998). We plan to use these relatively well-observed cases to develop and test a modeling/analysis system that utilizes satellite-based rainfall estimates and rainfall forecasts to forecast flooding and landslides associated with hurricanes and other heavy rain events. This would include determining the utility of existing multisatellite precipitation analyses (e.g., Grose et al., 2002) in flood and landslide analysis through the use of hydrological and landslide models. Figure 3 shows the 12-h forecast (for 00Z, 7/23/03) of rainfall and surface streamlines, made with the new Weather and Research Forecast Model (WRF) at 10-km resolution.



Figure 3. WRF model 12-h rain forecast. (Courtesy B. Shaw, FSL; see text and <u>www.wrf-model.org</u> for details.)

# 5. THE INTERAGENCY TEAM: NOAA, NASA AND USGS

The leadership team for the Continuum project consists of a few key personnel in NOAA-Boulder, NASA-Greenbelt, and USGS-Denver. Project scientists and engineers will be drawn from numerous research facilities in these three agencies. This is a bold experiment in sharing expertise toward a common goal that none of the three agencies could do alone. NASA scientists at the Goddard Space Flight Center, in Greenbelt, Maryland, will have the lead in satellite monitoring, rainfall estimation, processing and analysis. NOAA scientists at FSL, in Boulder, Colorado, will have the lead in assimilating the satellite observations to the estimation of rainfall in near real time and in storm tracking. The USGS Geologic Discipline, based in Denver, Colorado, will have the lead responsibility for landslide and flood modeling. In addition, various combinations of NASA,

USGS, and NOAA personnel from a variety of science centers across the country will be involved in the project, including the development of the central GIS, the deployment of worldwide weather workstations, the onsight scientific leads in the prototype area, the vegetation variability influence, the socioeconomic factors, aircraft-borne monitoring, antecedent archives, system verification, and training.

## 6. CONCLUSIONS

We believe that by careful integration of remotesensing and in-situ observations. and assimilation of these observations into highresolution mesoscale models with topographic forcing, prediction of tropical precipitation is possible at small spatial and temporal scales. The goal of the Continuum project is to link such analyses and forecasts with hydrological and landslide/debris flow models to produce useful probabilistic maps of landslides for local emergency management and other officials in a timely manner. We plan to demonstrate such a capability using the comprehensive datasets already available for Hurricane Georges (1998) over Puerto Rico and the Dominican Republic, and other case studies.

## 7. REFERENCES

R. Elsberry, "Predicting Hurricane Landfall Precipitation: Optimistic and Pessimistic Views from the Symposium on Precipitation Extremes," Bull. Amer. Meteor. Soc., vol 83 (11), pp. 1333–1339, September 2002.

A.M.E. Grose, E.A. Smith, H.-S. Chung, M.-L. Ou, B.-J. Sohn, and F.J. Turk, "Possibilities and Limitations for Quantitative Precipitation Forecasts using Nowcasting Methods and Geosynchronous Satellite Imagery," J. Appl. Meteor., vol 41, pp. 763–785, July 2002.

J. Hellin and M.J. Haigh, "Rainfall in Honduras during Hurricane Mitch," Weather, vol 54, pp. 350–359, November 1999.

G..J. Huffman,, R.F. Adler, E.F. Stocker, D.T. Bolvin, and E.J. Nelkin, "Analysis of TRMM 3-hourly multi-satellite precipitation estimates computed in both real and post-real time." Preprints, 12th Conf. on Sat. Meteor. and Oceanog., Long Beach, CA, 6 pp, January 2003.

J.L. Mahoney, B.G. Brown, J.E. Hart, and C. Fischer, "Using Verification Techniques to Evaluate Differences Among Convective Forecasts," 16<sup>th</sup> Conf. on Probability and Statistics in the Atmospheric Sciences, Orlando, FL, Amer. Meteor. Soc., pp. 12–19, January 2002.

J.A. McGinley, S. Albers, and P. Stamus, "Validation of a Composite Convective Index as Defined by a Real-Time Local Analysis System," Wea. Forecasting, Amer. Met. Soc., vol 6, pp. 337–356, September 1991.

G. Padgett, "Monthly Global Tropical Cyclone Summary: October 1998." <u>http://www.hcane.com.tropcl.html</u>, November 1998.